

WIDE-AREA WALK-BEHIND COMMERCIAL MOWERS

- G 1332
- G 1336
- G 1548
- H 1536
- H 1748
- H 1952

FEATURES

GEAR- OR HYDROSTATIC-
DRIVE SYSTEMS

13, 15, 17 OR 19 HP*
KAWASAKI® ENGINES

DUAL-LEVER CONTROLS

BAGGER, SULKY
AND MULCH KIT
ATTACHMENTS

2-YEAR LIMITED
COMMERCIAL
WARRANTY†



MOW ANYWHERE.

All of our equipment is designed to be durable, and our walk-behind mowers are no exception. Tougher than the bolted design found on many mowers, Cub Cadet Commercial walk-behind mowers feature fully welded one-piece engine platforms and mowing decks. And the 7-gauge steel skirts are reinforced with solid-steel plates for extra strength and protection. Plus, with the Command Cut System,™ your customers will get a smooth, quality cut.

SEVERAL MODELS AVAILABLE

Our walk-behind mowers are available with 32," 36," 48" and 52" decks, so you can match your unit to your mowing needs. You can also choose from gear-drive units or hydrostatic-drive models.



DUAL-LEVER CONTROLS

With easy pistol-grip controls, the hydrostatic models provide simple on-the-go tracking adjustments.



TACKLE TOUGH TERRAIN

Patented Vari-Touch foot controls let you adjust drive-belt tension on the go from 8 to 24 lbs., which gives you better traction on wet or hilly terrain.



COMMERCIAL
MOWING
EQUIPMENT

*as rated by engine manufacturer †See specifications for warranty information.

WALK-BEHIND COMMERCIAL MOWERS



Gear-Drive Models

ENGINE	G 1332	G 1336	G 1548
Engine type	13 HP* Kawasaki® V-Twin OHV	13 HP* Kawasaki® V-Twin OHV	15 HP* Kawasaki® V-Twin OHV
Engine start	Recoil		
Engine lubrication	Full-pressure w/spin-on oil filter		
Fuel capacity	5-gallon tank		
TRANSMISSION			
Transmission	5-speed Peerless®		
Ground speed (max.)	6 mph		
Controls	Light-touch pistol grip		
Handle	1-1/4" outer diameter		
Brakes	Band on drum		
TIRES			
Front tires	9" x 3.5" - 4", no flat		
Front bearings	Bronze bushing, greasable		
Rear tires	13" x 6.5" - 6"		
Rear bearings	Ball bearing, greasable		
MOWING DECK			
Deck PTO	Manual		
Deck size	32"	36"	48"
Deck style	Fixed fabricated		
Deck construction	10-gauge		
Deck drive	Belt drive Kevlar®		
Deck blades	2	2	3
Cutting height adjustment	2" - 4"		
Blade spindle	Tapered-roller spindle bearing		
DIMENSIONS			
Weight (approx.)	403 lbs.	460 lbs.	480 lbs.
WARRANTY†			
2-year limited commercial			

Hydrostatic-Drive Models

ENGINE	H 1536	H 1748	H 1952
Engine type	15 HP* Kawasaki® V-Twin OHV	17 HP* Kawasaki® V-Twin OHV	19 HP* Kawasaki® V-Twin OHV
Engine start	Recoil	Electric	Electric
Engine lubrication	Full-pressure w/spin-on oil filter		
Fuel capacity	5-gallon tank		
TRANSMISSION			
Transmission	Dual Hydro-Gear™ 10cc pumps and Parker® wheel motors		
Ground speed (max.)	7 mph		
Controls	Dual hydro pistol grip		
Handle	1-1/4" outer diameter		
Brakes	Internal drum		
TIRES			
Front tires	9" x 3.5" - 4", no flat		
Front bearings	Bronze bushing, greasable		
Rear tires	16" x 6.5" - 8"		
Rear bearings	In wheel motors		
MOWING DECK			
Deck PTO	Manual		
Deck size	36"	48"	52"
Deck style	Fixed fabricated		
Deck construction	10-gauge		
Deck drive	Belt drive Kevlar®		
Deck blades	2	3	3
Cutting height adjustment	2" - 4"		
Blade spindle	Tapered-roller spindle bearing		
DIMENSIONS			
Weight (approx.)	534 lbs.	550 lbs.	641 lbs.
WARRANTY†			
2-year limited commercial			

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

*as rated by engine manufacturer

†See your local Cub Cadet Independent Dealer for warranty details.

Commercial products are intended for professional use.

773-03686 Printed in U.S.A. 12/08 © 2009 Cub Cadet